

DEFINITION OF TERMS

Air sharing - Sharing of an air supply between divers.

ATA(s) - “Atmospheres Absolute”, Total pressure exerted on an object, by a gas or mixture of gases, at a specific depth or elevation, including normal atmospheric pressure.

Breath-hold Diving - A diving mode in which the diver uses no self-contained or surface-supplied air or oxygen supply.

Buddy Breathing - Sharing of a single air source between divers.

Buddy Diver - Second member of the dive team.

Buddy System - Two comparably equipped scuba divers in the water in constant communication.

Buoyant Ascent - An ascent made using some form of positive buoyancy.

Burst Pressure - Pressure at which a pressure containment device would fail structurally.

Certified Diver - A diver who holds a recognized valid certification from an organizational member or internationally recognized certifying agency.

Controlled Ascent - Any one of several kinds of ascents including normal, swimming, and air sharing ascents where the diver(s) maintain control so a pause or stop can be made during the ascent.

Cylinder - A pressure vessel for the storage of gases.

Decompression Chamber - A pressure vessel for human occupancy. Also called a hyperbaric chamber or decompression chamber.

Decompression Sickness - A condition with a variety of symptoms, which may result from gas, and bubbles in the tissues of divers after pressure reduction.

Dive - A descent into the water, an underwater diving activity utilizing compressed gas, an ascent, and return to the surface.

Dive Computer- A microprocessor based device which computes a diver's theoretical decompression status, in real time, by using pressure (depth) and time as input to a decompression model, or set of decompression tables, programmed into the device.

Dive Location - A surface or vessel from which a diving operation is conducted.

Dive Site - Physical location of a diver during a dive.

Dive Table - A profile or set of profiles of depth-time relationships for ascent rates and breathing mixtures to be followed after a specific depth-time exposure or exposures.

Diver - An individual in the water who uses apparatus, including snorkel, which supplies breathing gas at ambient pressure.

Diver-In-Training - An individual gaining experience and training in additional diving activities under the supervision of a dive team member experienced in those activities.

Diver-Carried Reserve Breathing Gas - A diver-carried independent supply of air or mixed gas (as appropriate) sufficient under standard operating conditions to allow the diver to reach the surface, or another source of breathing gas, or to be reached by another diver.

Diving Mode - A type of diving required specific equipment, procedures, and techniques, for example, snorkel, scuba, surface-supplied air, or mixed gas.

Diving Control Board (DCB) - Group of individuals who act as the official representative of the membership organization in matters concerning the scientific diving program (Section 1.24).

Diving Safety Officer (DSO) - Individual responsible for the safe conduct of the scientific diving program of the membership organization (Section 1.20).

EAD - Equivalent Air Depth (see below).

Emergency Ascent - An ascent made under emergency conditions where the diver exceeds the normal ascent rate.

Enriched Air (EAN_x) - A name for a breathing mixture of air and oxygen when the percent of oxygen exceeds 21%. This term is considered synonymous with the term “nitrox” (Section 7.00).

Equivalent Air Depth (EAD) - Depth at which air will have the same nitrogen partial pressure as the nitrox mixture being used. This number, expressed in units of feet seawater or saltwater, will always be less than the actual depth for any enriched air mixture.

fN₂ - Fraction of nitrogen in a gas mixture, expressed as either a decimal or percentage, by volume.

fO₂ - Fraction of oxygen in a gas mixture, expressed as either a decimal or percentage, by volume.

FFW – Feet of freshwater, or equivalent static head.

FSW - Feet of seawater, or equivalent static head.

Hookah Diving - A type of shallow water surface-supplied diving where there is no voice communication with the surface.

Hyperbaric Chamber - See decompression chamber.

Hyperbaric Conditions - Pressure conditions in excess of normal atmospheric pressure at the dive location.

Lead Diver - Certified scientific diver with experience and training to conduct the diving operation.

Maximum Working Pressure - Maximum pressure to which a pressure vessel may be exposed under standard operating conditions.

Organizational Member - An organization which is a current member of the AAUS, and which has a program, which adheres to the standards of the AAUS as, set forth in the AAUS Standards for Scientific Diving Certification and Operation of Scientific Diving Programs.

Mixed Gas - MG

Mixed-Gas Diving - A diving mode in which the diver is supplied in the water with a breathing gas other than air.

MOD - Maximum Operating Depth, usually determined as the depth at which the pO₂ for a given gas mixture reaches a predetermined maximum.

MSW - Meters of seawater or equivalent static head.

Nitrox - Any gas mixture comprised predominately of nitrogen and oxygen, most frequently containing between 21% and 40% oxygen. Also be referred to as Enriched Air Nitrox, abbreviated EAN.

NOAA Diving Manual: Refers to the *NOAA Diving Manual, Diving for Science and Technology*, 2001 edition. National Oceanic and Atmospheric Administration, Office of Undersea Research, US Department of Commerce.

No-Decompression limits - Depth-time limits of the “no-decompression limits and repetitive dive group designations table for no-decompression air dives” of the U.S. Navy Diving Manual or equivalent limits.

Normal Ascent - An ascent made with an adequate air supply at a rate of 60 feet per minute or less.

Oxygen Clean - All combustible contaminants have been removed.

Oxygen Compatible - A gas delivery system that has components (o-rings, valve seats, diaphragms, etc.) that are compatible with oxygen at a stated pressure and temperature.

Oxygen Service - A gas delivery system that is both oxygen clean and oxygen compatible.

Oxygen Toxicity Unit - OTU

Oxygen Toxicity - Any adverse reaction of the central nervous system (“acute” or “CNS” oxygen toxicity) or lungs (“chronic”, “whole-body”, or “pulmonary” oxygen toxicity) brought on by exposure to an increased (above atmospheric levels) partial pressure of oxygen.

Pressure-Related Injury - An injury resulting from pressure disequilibrium within the body as the result of hyperbaric exposure. Examples include: decompression sickness, pneumothorax, mediastinal emphysema, air embolism, subcutaneous emphysema, or ruptured eardrum.

Pressure Vessel - See cylinder.

pN₂ - Inspired partial pressure of nitrogen, usually expressed in units of atmospheres absolute.

pO₂ - Inspired partial pressure of oxygen, usually expressed in units of atmospheres absolute.

Psi - Unit of pressure, “pounds per square inch.

Psig - Unit of pressure, “pounds per square inch gauge.

Recompression Chamber - see decompression chamber.

Scientific Diving - Scientific diving is defined (29CFR1910.402) as diving performed solely as a necessary part of a scientific, research, or educational activity by employees whose sole purpose for diving is to perform scientific research tasks.

Scuba Diving - A diving mode independent of surface supply in which the diver uses open circuit self-contained underwater breathing apparatus.

Standby Diver - A diver at the dive location capable of rendering assistance to a diver in the water.

Surface Supplied Diving - A diving mode in which the diver in the water is supplied from the dive location with compressed gas for breathing.

Swimming Ascent - An ascent, which can be done under normal or emergency conditions accomplished by simply swimming to the surface.

Umbilical - Composite hose bundle between a dive location and a diver or bell, or between a diver and a bell, which supplies a diver or bell with breathing gas, communications, power, or heat, as appropriate to the diving mode or conditions, and includes a safety line between the diver and the dive location.

Working Pressure - Normal pressure at which the system is designed to operate.